

WP 1307

TEAK TREAT (BOROQUAT)

A wood treatment chemical which eradicates and prevents mould & algae growth on teak boat decks and any other teak wood exposed to the elements.



BENEFITS

- Eradicates mould and algae growth.
- Prevents regrowth.
- Improves appearance of teak giving a more uniform appearance over time.
- No hard work or scrubbing.

DESCRIPTION

Teak Treat is a dual purpose product which works by dislodging the black biological residues which can blight a decks appearance.

Its primary use is for treating tired decks which are not soiled with oil or diesel but are in need of a refresh.

Over several weeks it will restore the wood back to a uniform appearance with a lighter colour overall.

Please note, there will be NO immediate visible improvement but, over the following weeks, you will see a general lightening of the deck and a significantly improved appearance. Mould, algae and algae spots should disappear. Teak Treat allows the elements to wash them away.

Secondly it can be used as an overwintering solution to preserve the appearance of the wood and prevent greening.

PRODUCT SIZES

- 1 litre
- 3.25 litre
- 5 litre

INSTRUCTIONS FOR USE

Teak Treat must be applied to a dry deck. It is normally diluted with between 1 and 3 parts water to 1-part Teak Treat.

Apply liberally to the deck so that the surface is saturated.

Simply leave the deck and over the course of the next few weeks you will see an improvement to any tired decks and protection from black and green marks.

For best results, treat on a dry day and repeat ten days later. Teak Treat works best when exposed to sunshine.

By using this method, some customers have reported their decks to be maintained for up to 2 years.

PHYSICAL PROPERTIES

Colour: Brown.

Appearance: Brown liquid.

Odour: Characteristic.

Solubility: Soluble in water.

Boiling point: No data available.

Flash point: No data available.

Flammability: Non-flammable.

Density: 1.054g/cm³

pH: 7.4.

Wessex Chemical Factors Ltd
9 Crane Way
Woolsbridge Industrial Park
Three Legged Cross
Wimborne
Dorset
BH21 6FA
United Kingdom

Tel: 01202 823699

Fax: 01202 813863

Email: info@wessexchemicalfactors.co.uk

Website: www.wessexboatstore.co.uk



HEALTH & SAFETY

Hazard pictograms (CLP):



Hazard statements (CLP):

H315 – Causes skin irritation.

H319 – Causes serious eye irritation.

H360 – May damage fertility or the unborn child.

H411 – Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP):

P201 – Obtain special instructions before use.

P202 – Do not handle until all safety precautions have been read and understood.

P264 – Wash hands thoroughly after handling.

P273 – Avoid release to the environment.

P280 – Wear eye protection, protective gloves.

P302+P352 – IF ON SKIN. Wash with plenty of water.

P305+P351+P338 – IF IN EYES. Rinse cautiously with water for several minutes.

Remove contact lenses if present and easy to do so. Continue rinsing.

P308+P313 – If exposed or concerned: Get medical advice/attention.

P332+P313 – If skin irritation occurs: Get medical advice/attention.

P337+P313 – If eye irritation persists: Get medical advice/attention.

P362+P364 – Take off contaminated clothing and wash before reuse.

P391 – Collect spillage.

P405 – Store locked up.

P501 – Dispose of contents/container at hazardous or specialist waste collection point, in accordance with local, regional, national and/or international regulation

Hazardous ingredients: Disodium octaborate.

EUH210 – Safety Data Sheet available on request.

