

# WP

## FDS1

Fast drying solvent cleaner, good at removing flux and grease without damage to plastic or electrical components.



### BENEFITS

- Powerful solvent action.
- Rapid evaporation.
- Non-conductive, recommended in the maintenance of electrical contacts and equipment.
- Can remove mould, grease, some glues, dirt, tar, wax, oil, dust and more.

### PRODUCT SIZES

- 500ml aerosol
- 500ml aerosol (doz.)
- 5 litres

### DESCRIPTION

FDS1 is a powerful degreasant formulated without chlorinated solvents. The flushing action of the product when used with a solvent resistant pressurised sprayer quickly disposes of grease, oil, wax, tar and other deposits without solvent wastage.

FDS1 will not corrode any metals or alloys and is recommended in the maintenance of electrical contacts and equipment, spot removal in the textiles and associated industries and also an invaluable mould cleaner within the plastics industry.

### INSTRUCTIONS FOR USE

Always check small area for compatibility.

With 5 litre bottles - always put cap back on container when not in use.

Aerosols – shake well before use. Hold can as upright as possible and spray evenly on to surface to be worked on.

## HEALTH & SAFETY

Hazard pictograms (CLP):



Hazard statements (CLP):

H222 - Extremely flammable aerosol.  
H229 – Pressurised container: May burst if heated.  
H304 – May be fatal if swallowed and enters airways.  
H315 – Causes skin irritation.  
H319 – Causes serious eye irritation.  
H336 – May cause drowsiness or dizziness.  
H411 – Toxic to aquatic life with long lasting effect.

## PHYSICAL PROPERTIES

**Colour:** Colourless.  
**Appearance:** Aerosol.  
**Odour:** Characteristic.  
**Solubility:** In water, material is partially soluble.  
**Boiling point:** No data available.  
**Flash point:** <0°C  
**Flammability:** Extremely flammable aerosol.  
**Density:** No data available.  
**pH:** N/a.

**Wessex Chemical Factors Ltd**  
9 Crane Way  
Woolsbridge Industrial Park  
Three Legged Cross  
Wimborne  
Dorset  
BH21 6FA  
United Kingdom

Tel: 01202 823699  
Fax: 01202 813863  
Email: [info@wessexchemicalfactors.co.uk](mailto:info@wessexchemicalfactors.co.uk)  
Website: [www.wessexboatstore.co.uk](http://www.wessexboatstore.co.uk)



## HEALTH & SAFETY (Cont.)

Precautionary statements (CLP):

P210 – Keep away from heat, hot surfaces, sparks, open flames and ignition sources. No smoking.  
P251 – Do not pierce or burn even after use.  
P261 – Avoid breathing mist, spray, vapours.  
P264 – Wash hands thoroughly after handling.  
P271 – Use only outdoors or in a well-ventilated area.  
P273 – Avoid release to the environment.  
P280 – Wear eye protection, protective gloves, protective clothing.  
P301+P310 – IF SWALLOWED: Immediately call a doctor, a POISON CENTRE.  
P302+P352 – IF ON SKIN: Wash with plenty of water.  
P304+P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.  
P312 – Call a doctor, a POISON CENTRE if you feel unwell.  
P321 – Specific treatment (see supplemental first instructions on label).  
P331 – Do NOT induce vomiting.  
P332+P313 – If skin irritation occurs: Get medical advice/attention.  
P337+P313 – If eye irritation persists: Get medical advice/attention.  
P362+P364 – Take off contaminated clothing and wash before reuse.  
P391 – Collect spillage.  
P403+P233 – Store in a well-ventilated place. Keep container tightly closed.  
P405 – Store locked up.  
P410+P412 – Protect from sunlight. Do not expose to temperatures exceeding 50°C, 122°F.  
P501 – Dispose of contents/container to hazardous or specialist waste collection point, in accordance with local, regional, national and/or international regulation.  
**Hazardous ingredients:**  
Propan-2-ol, isopropyl alcohol, isopropanol, Hydrocarbons, C6, isoalkanes, < 5% hexane.

**EUH210 – Safety Data Sheet available on request.**

