

WP

RUST BUSTER 500

Rust protector and lubricant



BENEFITS

- Protects tools, mechanisms, equipment and more against rust.
- Penetrates and loosens rusted components.
- Penetrates and lubricates to prevent squeaking.
- Drives out water on metal surfaces.
- Un-jams, lubricates and frees sticky mechanisms.
- Ideal for spraying on to router cutter shanks and saw blades to prevent rust.

DESCRIPTION

R500 Rust Protector and Lubricant is ideal for use in the engineering and construction industry for the maintenance and protection of cutting tools/blades and other machinery and equipment.

This solvent based formula evaporates, leaving a protective film with lubricating qualities, for long term protection.

Suitable for all metals, cutting tools, sawblades and router cutter shanks.

PRODUCT SIZES

- 500ml aerosol can.
- Dozen 500ml aerosol cans.
- Also available in 5 litre containers (non-aerosol).

INSTRUCTIONS FOR USE

Simply spray or brush R500 Rust Protector and Lubricant onto the surface and leave.

Available in liquid and aerosol form.

HEALTH & SAFETY

Hazard pictogram (CLP):



Hazard statements (CLP):

H226 – Flammable liquid and vapour.

H315 – Causes skin irritation.

H336 – May cause drowsiness or dizziness.

H411 – Toxic to aquatic life with long lasting effects.

EUH210 – Safety Data Sheet available on request.

HEALTH & SAFETY (Cont.)

Precautionary statements (CLP):

P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 – Keep container tightly closed.

P240 – Ground/bond container and receiving equipment.

P241 – Use explosion-proof electrical equipment.

P261 – Avoid breathing vapours, spray, mist.

P264 – Wash hands thoroughly after handling.

P271 – Use only outdoors or in a well-ventilated area.

P273 – Avoid release to the environment.

P280 – Wear eye protection, protective gloves.

P302+P352 – IF ON SKIN: Wash with plenty of water.

P303+P361+P353 – IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 – Call a POISON CENTRE/doctor if you feel unwell.

P332+P313 – If skin irritation occurs: Get medical advice/attention.

P362+P364 – Take off contaminated clothing and wash it before reuse.

P370+P378 – In case of fire: Use dry sand, dry extinguishing powder, carbon dioxide (CO₂), foam, Water spray or fog, to extinguish.

P391 – Collect spillage.

P403+P233 – Store in a well-ventilated place. Keep container tightly closed.

P403+P235 – Store in a well-ventilated place. Keep cool.

P405 – Store locked up.

P501 – Dispose of contents/container to a hazardous or specialist waste collection point, in accordance with local, regional, national and/or international regulation.

Hazardous ingredients:

Distillates (petroleum), hydrotreated light, Kerosine – unspecified [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150°C to 290°C (302°F to 554°F).]

PHYSICAL PROPERTIES

Colour: Colourless.

Appearance: Liquid.

Odour: Characteristic.

Solubility: No data available.

Boiling point: No data available.

Flash point: No data available.

Flammability: Non-flammable.

Density: No data available.

pH: N/a.

Wessex Chemical Factors Ltd

17 Crane Way

Woolsbridge Industrial Park

Three Legged Cross

Wimborne

Dorset

BH21 6FA

United Kingdom

Tel: 01202 823699

Fax: 01202 813863

Email: info@wessexchemicalfactors.co.uk

Website: www.wessexboatstore.co.uk

