

WP 2203

Wessex Teak Sealer



An emulsion-based sealer that seals and protects teak and brings out the natural colour of the wood.

BENEFITS

- Absorbs into wood & brings out the natural colour.
- Overtime forms cross links for longer life and resistance to staining.
- Contains no pigment.
- Contains a UV Protector to reduce UV damage.
- Protects against mould/mildew, moisture & colour loss.

DESCRIPTION

Wessex Teak Sealer is an emulsion-based sealer containing a high quality tung oil.

On application it is absorbed into the wood and brings out the natural colour.

Over time the sealer forms cross links which means it lasts longer and provides better resistance to stains, mould/mildew and moisture.

Wessex Teak Sealer also contains an innovative UV Protector that protects teak from the effects of the sun. The protector absorbs UV rays which helps to maintain the colour of the wood.

Once treated wood is dried, the appearance will be maintained for at least 12 months.

PRODUCT SIZES

- 500ml tin.
- 1 litre tin.

INSTRUCTIONS FOR USE

Coverage – approximately 4 square metres per 1 litre of teak sealer

Directions

Stir the contents of the tin well before use.

We recommend cleaning the whole area with Wessex Teak Cleaner and Renovator prior to treatment to ensure that all dirt and growths have been removed.

Prior to treatment, ensure that the surface is dry and free from debris.

Apply teak sealer with a brush ensuring that the area is fully covered, and that the product is worked into the grain.

Leave to dry for approximately one hour.

HEALTH & SAFETY

Hazard pictograms (CLP): None

Hazard statements (CLP):

None

HEALTH & SAFETY (Cont.)

Precautionary statements (CLP):

None

Hazardous ingredients:

None

EUH210 – Safety Data Sheet available on request.

PHYSICAL PROPERTIES

Colour: Colourless

Appearance: liquid.

Odour: characteristic

Solubility: No data available

Boiling point: No data available.

Flash point: No data available.

Flammability: Non-flammable.

Density: 0.97g/cm³.

pH: No data available

Wessex Chemical Factors Ltd

17 Crane Way

Woolsbridge Industrial Park

Three Legged Cross

Wimborne

Dorset

BH21 6FA

United Kingdom

Tel: 01202 823699

Fax: 01202 813863

Email: info@wessexchemicalfactors.co.uk

Website: www.wessexboatstore.co.uk



Teak Sealer

21/7/23

page 2